



TESTING

- 1.100% Open&Short&Miss-Wire testing
- 2.Contact Resistance:2Ω MAX.
- 3.Insulation Resistance:50MΩ/250V DC MIN.
- 4.This product is ROHS compliant.

H	CABLE:OD7.5 1P(TWISTED)/20AWG+2C/20AWG+A1 BLACK PVC	915	MM
G	CABLE:OD7.5 1P(TWISTED)/20AWG+2C/20AWG+A1 BLACK PVC	530	MM
F	CABLE:OD7.5 1P(TWISTED)/20AWG+2C/20AWG+A1 BLACK PVC	630	MM
E	DETUSCH:HD10-6-12P GRAY CONNECTOR	1	SET
D	OBD2 FEMALE:MOLEX 51115-1621 with 2 TPA Locks BLACK	1	SET
C	OBD2 FEMALE OVER-MOULD:BLACK PVC	35	G
B	OBD2 FEMALE CONNECTOR:PA66+GF	1	SET
A	DETUSCH:HD16-6-12S-B010 GRAY CONNECTOR	1	SET
ITEM	BILL OF MATERIAL /SPECIFICATION	QTY	UNIT

PIN ASSIGNMENT			
P4 J1708 MALE	P1 J11708 FEMALE	P2 OBD2 F	P3 OBD2 F
A	A ORANGE	10	10
B	B BROWN	2	2
E	E RED	4	4
C	C GND	16	16
D	D	6	6
F	F	14	14

