



P3 Bullet Terminal*7

P2 JST PHDR-12VS



PIN ASSIGNMENT

P3 Terminal	P1 OBD2 24V MALE	P2 JST 12P
	16	AWG22 RED 2
	16	AWG22 BLUE 4
	4	AWG22 BLACK 8
	6	AWG24 GREEN 10
	14	AWG24 WHITE 12
⊙	AWG22	AWG24 BROWN 1
⊙	AWG22	AWG24 ORANGE 3
⊙	AWG22	AWG24 PURPLE 5
⊙	AWG22	AWG24 YELLOW 6
⊙	AWG22	AWG24 GRAY 7
⊙	AWG22	AWG24 PINK 9
⊙	AWG22	AWG24 LT-GREEN 11

TESTING
 1.100% Open&Short&Miss-Wire testing
 2.Contact Resistance:2Ω MAX.
 3.Insulation Resistance:50MΩ/250V DC MIN.
 4.This product is ROHS compliant.

F	UL1007 22AWG WIRE	500	mm
E	CABLE:OD:7.0MM 1P/24AWG+3C/22AWG+7C/AWG24+AL BLACK	3000	mm
D	Hu Lane Bullet Terminal : 67011040BS2	7	SET
C	JST CONNECTOR WHITE :PHDR-12VS	1	SET
B	OBD2 MALE BLACK SHELL ABS+PC	35	G
A	OBD2 24V MALE BLACK CONNECTOR PA66	1	SET
ITEM	BILL OF MATERIAL /SPECIFICATION	QTY	UNIT

