





Product Description

FH Auxiliary cameras are cameras connected to DCC07-12 or FleetFlix Al+ Pro dashcams. When connected to the dashcam, the cameras enable live video and recording from the portal of additional perspectives during trips. The cameras are installed around the vehicle in key locations. All auxiliary cameras include a 64 GB SD card that stores approximately 100 hours of recordings. When the SD card is full, new recordings overwrite the oldest recordings. Provide your fleet with 360° video coverage.

Features

- · Wired and Wi-Fi options available
- Adjustable event/trigger setting levels
- Provide vehicle 360° coverage
- Mouting options available flush/wrap/magnets
- Night view distance 30ft (9.14 m)
- Enjoy a field of view horizontal: 106°; vertical: 55.8°; diagonal: 126°
- Automatic server upload based on events prevents driver tampering of SD card
- Incorporated within Geotab, the camera system allows any vehicle rule within Geotab to activate a video event

PRODUCT SPECIFICATIONS

AVAILABLE MODELS

Wi-Fi Flush, Wi-Fi Wrap, Wired Flush, Wired Wrap

IP RATING

IP69K

POWER

12V or 24V DC

OPERATING ENVIRONMENT

Temperature infrared on: -4° to 104° F (-20° to 40° C) Temperature infrared off: -4° to 140° F (-20° to 60° C) Humidity: 20% to 55%, non-condensing

RESOLUTION

Up to 1080p, 30 frames per second

3.5*1.5*3.5 in (8.9*3.9*8.9 cm)

STREAMING AND RECORDING

720p, 30 frames per second

3.3 mm with day and night functionality

WEIGHT

.99 lb (449 grams)

FLEET HOSTER 678.759.2544

- ✓ S∧LES@FLEETHOSTER.COM
- ₩WW.FLEETHOSTER.COM

