

Product Description

The RTR01-1000 incorporates state-of-the-art wireless technology for enhanced performance and expanded functionality. Experience a stable wireless signal with increased scalability, boasting a maximum transmission rate of up to 1200Mbps (requires the 11ac PCIE mode). Enjoy 2.4GHz speeds of up to 300Mbps with 4G LTE, this device ensures stability when connected to dash cameras and auxiliary fleet cameras. Additionally, it features a watchdog function and offers 1 USB 2.0 interface along with 1 Micro SD slot for added versatility.

Features

- Direct connection into Geotab device loX port
- Optimum range and rugged design
- 1 USB 2.0 interface
- 1 Micro SD Card Slot
- Support 3G/4G
- WiFi Option Available
- T-Mobile, AT&T, and Verizon networks
- 5dbi high-gain omni antennas

PRODUCT **SPECIFICATIONS**

DIMENSIONS 141*85*26MM

FDD:B2/B4/B5/B12/B13/B14/B66/B71

WORK FREQUENCY 2.4GHz

OPERATING TEMPERATURE -20°C ~ 70°C;

RAM DDR 128MB

WIRELESS RATE Max 300Mbps

CHIPSET QCA 9531

MAX POWER CONSUMPTION

FLEET HOSTER 678.759.2544

- O MCDONOUGH, GA 30253

